

# Sequence Alignment/Map Optional Fields Specification

The SAM/BAM Format Specification Working Group

22 May 2018

The master version of this document can be found at <https://github.com/samtools/hts-specs>. This printing is version b1ae9f9 from that repository, last modified on the date shown above.

This document is a companion to the *Sequence Alignment/Map Format Specification* that defines the SAM and BAM formats, and to the *CRAM Format Specification* that defines the CRAM format.<sup>1</sup> Alignment records in each of these formats may contain a number of optional fields, each labelled with a *tag* identifying that field's data. This document describes each of the predefined standard tags, and discusses conventions around creating new tags.

## 1 Standard tags

Predefined standard tags are listed in the following table and described in greater detail in later subsections. Optional fields are usually displayed as **TAG:TYPE:VALUE**; the *type* may be one of **A** (character), **B** (general array), **f** (real number), **H** (hexadecimal array), **i** (integer), or **Z** (string).

Tag	Type	Description
AM	i	The smallest template-independent mapping quality of segments in the rest
AS	i	Alignment score generated by aligner
BC	Z	Barcode sequence identifying the sample
BQ	Z	Offset to base alignment quality (BAQ)
BZ	Z	Phred quality of the unique molecular barcode bases in the <b>OX</b> tag
CB	Z	Cell identifier
CC	Z	Reference name of the next hit
CG	B,I	BAM only: <b>CIGAR</b> in BAM's binary encoding if (and only if) it consists of >65535 operators
CM	i	Edit distance between the color sequence and the color reference (see also <b>NM</b> )
CO	Z	Free-text comments
CP	i	Leftmost coordinate of the next hit
CQ	Z	Color read base qualities
CR	Z	Cellular barcode sequence bases (uncorrected)
CS	Z	Color read sequence
CT	Z	Complete read annotation tag, used for consensus annotation dummy features
CY	Z	Phred quality of the cellular barcode sequence in the <b>CR</b> tag
E2	Z	The 2nd most likely base calls
FI	i	The index of segment in the template
FS	Z	Segment suffix
FZ	B,S	Flow signal intensities
GC	?	Reserved for backwards compatibility reasons
GQ	?	Reserved for backwards compatibility reasons
GS	?	Reserved for backwards compatibility reasons
HO	i	Number of perfect hits
H1	i	Number of 1-difference hits (see also <b>NM</b> )

<sup>1</sup>See [SAMv1.pdf](#) and [CRAMv3.pdf](#) at <https://github.com/samtools/hts-specs>.

H2	i	Number of 2-difference hits
HI	i	Query hit index
IH	i	Number of stored alignments in SAM that contains the query in the current record
LB	Z	Library
MC	Z	CIGAR string for mate/next segment
MD	Z	String for mismatching positions
MF	?	Reserved for backwards compatibility reasons
MI	Z	Molecular identifier; a string that uniquely identifies the molecule from which the record was derived
MQ	i	Mapping quality of the mate/next segment
NH	i	Number of reported alignments that contains the query in the current record
NM	i	Edit distance to the reference
OC	Z	Original CIGAR
OP	i	Original mapping position
OQ	Z	Original base quality
OX	Z	Original unique molecular barcode bases
PG	Z	Program
PQ	i	Phred likelihood of the template
PT	Z	Read annotations for parts of the padded read sequence
PU	Z	Platform unit
Q2	Z	Phred quality of the mate/next segment sequence in the R2 tag
QT	Z	Phred quality of the sample-barcode sequence in the BC (or RT) tag
QX	Z	Quality score of the unique molecular identifier in the RX tag
R2	Z	Sequence of the mate/next segment in the template
RG	Z	Read group
RT	Z	Barcode sequence (deprecated; use BC instead)
RX	Z	Sequence bases of the (possibly corrected) unique molecular identifier
S2	?	Reserved for backwards compatibility reasons
SA	Z	Other canonical alignments in a chimeric alignment
SM	i	Template-independent mapping quality
SQ	?	Reserved for backwards compatibility reasons
TC	i	The number of segments in the template
U2	Z	Phred probability of the 2nd call being wrong conditional on the best being wrong
UQ	i	Phred likelihood of the segment, conditional on the mapping being correct
X?	?	Reserved for end users
Y?	?	Reserved for end users
Z?	?	Reserved for end users

---

## 1.1 Additional Template and Mapping data

**AM:i:int** The smallest template-independent mapping quality of segments in the rest.

**AS:i:score** Alignment score generated by aligner.

**BQ:Z:qualities** Offset to base alignment quality (BAQ), of the same length as the read sequence. At the  $i$ -th read base,  $BAQ_i = Q_i - (BQ_i - 64)$  where  $Q_i$  is the  $i$ -th base quality.

**CC:Z:rname** Reference name of the next hit; '=' for the same chromosome.

**CG:B:I,encodedCigar** Real CIGAR in its binary form if (and only if) it contains >65535 operations. This is a BAM file only tag as a workaround of BAM's incapability to store long CIGARs in the standard way. SAM and CRAM files created with updated tools aware of the workaround are not expected to contain this tag. See also the footnote in Section 4.2 of the SAM spec for details.

**CP:i:pos** Leftmost coordinate of the next hit.

**E2:Z:bases** The 2nd most likely base calls. Same encoding and same length as SEQ. See also U2 for associated quality values.

**FI:i:int** The index of segment in the template.

**FS:Z:str** Segment suffix.

**H0:i:count** Number of perfect hits.

**H1:i:count** Number of 1-difference hits (see also NM).

**H2:i:count** Number of 2-difference hits.

**HI:i:i** Query hit index, indicating the alignment record is the *i*-th one stored in SAM.

**IH:i:count** Number of stored alignments in SAM that contains the query in the current record.

**MC:Z:cigar** CIGAR string for mate/next segment.

**MD:Z:[0-9]+((([A-Z]|\^[A-Z]) [0-9])\*)** String for mismatching positions.  
 The MD field aims to achieve SNP/indel calling without looking at the reference. For example, a string '10A5^AC6' means from the leftmost reference base in the alignment, there are 10 matches followed by an A on the reference which is different from the aligned read base; the next 5 reference bases are matches followed by a 2bp deletion from the reference; the deleted sequence is AC; the last 6 bases are matches. The MD field ought to match the CIGAR string.

**MQ:i** Mapping quality of the mate/next segment.

**NH:i** Number of reported alignments that contains the query in the current record.

**NM:i** Edit distance to the reference, including ambiguous bases but excluding clipping.

**PQ:i** Phred likelihood of the template, conditional on both the mapping being correct.

**Q2:Z:qualities** Phred quality of the mate/next segment sequence in the R2 tag. Same encoding as QUAL.

**R2:Z:bases** Sequence of the mate/next segment in the template. See also Q2 for any associated quality values.

**SA:Z:(*rname*, *pos*, *strand*, *CIGAR*, *mapQ*, *NM*;)+** Other canonical alignments in a chimeric alignment, formatted as a semicolon-delimited list. Each element in the list represents a part of the chimeric alignment. Conventionally, at a supplementary line, the first element points to the primary line. *Strand* is either '+' or '-', indicating positive/negative strand, corresponding to FLAG bit 0x10. *Pos* is a 1-based coordinate.

**SM:i** Template-independent mapping quality.

**TC:i** The number of segments in the template.

**U2:Z** Phred probability of the 2nd call being wrong conditional on the best being wrong. The same encoding and length as QUAL. See also E2 for associated base calls.

**UQ:i** Phred likelihood of the segment, conditional on the mapping being correct.

## 1.2 Metadata

**RG:Z:readgroup** The read group to which the read belongs. If @RG headers are present, then *readgroup* must match the RG-ID field of one of the headers.

**LB:Z:library** The library from which the read has been sequenced. If @RG headers are present, then *library* must match the RG-LB field of one of the headers.

**PG:Z** Program. Value matches the header PG-ID tag if @PG is present.

**PU:Z:platformunit** The platform unit in which the read was sequenced. If @RG headers are present, then *platformunit* must match the RG-PU field of one of the headers.

**CO:Z:text** Free-text comments.

### 1.3 Barcodes

**BC:Z:sequence** Barcode sequence (Identifying the sample/library), with any quality scores (optionally) stored in the QT tag. The BC tag should match the QT tag in length. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the barcodes and places a hyphen ('-') between the barcodes from the same template.

**QT:Z:qualities** Phred quality of the sample-barcode sequence in the BC (or RT) tag. Same encoding as QUAL, i.e., Phred score + 33. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the quality strings with spaces (' ') between the different strings from the same template.

**CB:Z:str** Cell identifier, consisting of the optionally-corrected cellular barcode sequence and an optional suffix. The sequence part is similar to the CR tag, but may have had sequencing errors etc corrected. This may be followed by a suffix consisting of a hyphen ('-') and one or more alphanumeric characters to form an identifier. In the case of the cellular barcode (CR) being based on multiple barcode sequences the recommended implementation concatenates all the (corrected or uncorrected) barcodes with a hyphen ('-') between the different barcodes. Sequencing errors etc aside, all reads from a single cell are expected to have the same CB tag.

**CR:Z:sequence+** Cellular barcode. The uncorrected sequence bases of the cellular barcode as reported by the sequencing machine, with the corresponding base quality scores (optionally) stored in CY. Sequencing errors etc aside, all reads with the same CR tag likely derive from the same cell. In the case of the cellular barcode being based on multiple barcode sequences the recommended implementation concatenates all the barcodes with a hyphen ('-') between the different barcodes.

**CY:Z:qualities+** Phred quality of the cellular barcode sequence in the CR tag. Same encoding as QUAL, i.e., Phred score + 33. The lengths of the CY and CR tags must match. In the case of the cellular barcode being based on multiple barcode sequences the recommended implementation concatenates all the quality strings with with spaces (' ') between the different strings.

**MI:Z:str** Molecular Identifier. A unique ID within the SAM file for the source molecule from which this read is derived. All reads with the same MI tag represent the group of reads derived from the same source molecule.

**OX:Z:sequence+** Raw (uncorrected) unique molecular identifier bases, with any quality scores (optionally) stored in the BZ tag. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the barcodes with a hyphen ('-') between the different barcodes.

**BZ:Z:qualities+** Phred quality of the (uncorrected) unique molecular identifier sequence in the OX tag. Same encoding as QUAL, i.e., Phred score + 33. The OX tags should match the BZ tag in length. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the quality strings with a space (' ') between the different strings.

**RX:Z:sequence+** Sequence bases from the unique molecular identifier. These could be either corrected or uncorrected. Unlike MI, the value may be non-unique in the file. Should be comprised of a sequence of bases. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the barcodes with a hyphen ('-') between the different barcodes.

If the bases represent corrected bases, the original sequence can be stored in OX (similar to OQ storing the original qualities of bases.)

**QX:Z:qualities+** Phred quality of the unique molecular identifier sequence in the RX tag. Same encoding as QUAL, i.e., Phred score + 33. The qualities here may have been corrected (Raw bases and qualities can be stored in OX and BZ respectively.) The lengths of the QX and the RX tags must match. In the case of multiple unique molecular identifiers (e.g., one on each end of the template) the recommended implementation concatenates all the quality strings with a space (' ') between the different strings.

**RT:Z:sequence** Deprecated alternative to BC tag originally used at Sanger.

## 1.4 Original data

**OC:Z:cigar** Original CIGAR, usually before realignment.

**OP:i:pos** Original 1-based mapping position, usually before realignment.

**OQ:Z:qualities** Original base quality, usually before recalibration. Same encoding as QUAL.

## 1.5 Annotation and Padding

**CT:Z:strand;type(;key(=value))\*** Complete read annotation tag, used for consensus annotation dummy features.

The CT tag is intended primarily for annotation dummy reads, and consists of a *strand*, *type* and zero or more *key=value* pairs, each separated with semicolons. The *strand* field has four values as in GFF3, and supplements FLAG bit 0x10 to allow unstranded ('.'), and stranded but unknown strand ('?') annotation. For these and annotation on the forward strand (*strand* set to '+'), do not set FLAG bit 0x10. For annotation on the reverse strand, set the *strand* to '-' and set FLAG bit 0x10.

The *type* and any *keys* and their optional *values* are all percent encoded according to RFC3986 to escape meta-characters '=', '%', ';', '|', or non-printable characters not matched by the `isprint()` macro (with the C locale). For example a percent sign becomes '%25'.

**PT:Z:start;end;strand;type(;key(=value))\*(\|start;end;strand;type(;key(=value)))\*** Read annotations for parts of the padded read sequence.

The PT tag value has the format of a series of tags separated by '|', each annotating a sub-region of the read. Each tag consists of *start*, *end*, *strand*, *type* and zero or more *key=value* pairs, each separated with semicolons. *Start* and *end* are 1-based positions between one and the sum of the M/I/D/P/S/=/X CIGAR operators, i.e. SEQ length plus any pads. Note any editing of the CIGAR string may require updating the 'PT' tag coordinates, or even invalidate them. As in GFF3, *strand* is one of '+' for forward strand tags, '-' for reverse strand, '.' for unstranded or '?' for stranded but unknown strand. The *type* and any *keys* and their optional *values* are all percent encoded as in the CT tag.

## 1.6 Technology-specific data

**FZ:B:S,intensities** Flow signal intensities on the original strand of the read, stored as `(uint16_t) round(value * 100.0)`.

### 1.6.1 Color space

**CM:i:distance** Edit distance between the color sequence and the color reference (see also NM).

**CS:Z:sequence** Color read sequence on the original strand of the read. The primer base must be included.

**CQ:Z:qualities** Color read quality on the original strand of the read. Same encoding as QUAL; same length as CS.

## 2 Locally-defined tags

You can freely add new tags. Note that tags starting with 'X', 'Y', or 'Z' and tags containing lowercase letters in either position are reserved for local use and will not be formally defined in any future version of this specification.

If a new tag may be of general interest, it may be useful to have it added to this specification. Additions can be proposed by opening a new issue at <https://github.com/samtools/hts-specs/issues> and/or by sending email to [samtools-devel@lists.sourceforge.net](mailto:samtools-devel@lists.sourceforge.net).

## Appendix A Tag History

This appendix lists when standard tags were initially defined or significantly changed, and other historical events that affect how tags are interpreted or what files they may appear in.

### May 2018

Cellular barcode tags CB, CR, and CY added.

### November 2017

SAM version number `VN:1.6` introduced, indicating the addition of the CG tag representation of very long CIGAR strings. Files that contain records with more than 65,535 CIGAR operators should not declare a version number lower than 1.6 in their `@HD` headers.

### August 2017

Unique molecular identifier tags BZ, MI, OX, QX, and RX added.  
Usage of sample barcode tag BC clarified.

### June 2017

Corrected the description of the E2 (second-most-likely bases) tag, which was previously unclear as to whether it contains bases or base qualities.

### September 2016

Predefined tags, previously listed as a brief table within the main SAM specification, have been split out into this new document. There is now space for clearer and more complete tag descriptions.

### February 2014

MC tag added.

### May 2013

SAM version number `VN:1.5` introduced, with limited impact for tags other than indicating that the CT/PT annotation tag definitions are considered finalised.

SA tag added.

### March 2012

Descriptions of CT and PT annotation tags significantly clarified.

### October 2011

Sample barcode tags QT and RT added, with RT being identified as a deprecated alternative to BC.  
Read annotation tags CT and PT added.

### September 2011

FZ tag's type changed from H to B,S-array.  
BC and CO tags added.

## April 2011

SAM version number `VN:1.4` introduced, indicating the addition of the B-array tag type. Files that contain records with B-array fields should not declare a version number lower than 1.4 in their `@HD` headers.

FZ tag added, with type H.

MD tag description changed to allow IUPAC ambiguity codes in addition to `ACGTN`.

## March 2011

CC and CP tags reinstated with their original meanings.

## November 2010

BQ tag added.

## July 2010

The specification was rewritten as a `LATEX` document specifying SAM version number `VN:1.3`.

Tags FI, FS, OC, OP, OQ, and TC added.

Tags GC, GQ, and GS listed as reserved for backwards compatibility.

Existing CC, CP, and MF tags removed and noted as reserved for backwards compatibility.

## July 2009

The original SAM “0.1.2-draft” specification specified version number `VN:1.0` and defined a total of thirty standard tags:

AM	CS	IH	NM	RG
AS	E2	LB	PG	S2
CC	H0	MD	PQ	SM
CM	H1	MF	PU	SQ
CP	H2	MQ	Q2	U2
CQ	HI	NH	R2	UQ

At this time, SQ and S2 were already deprecated in favour of E2 and U2.